

---

**Data Recipient Report for the  
Janssen Clinical Trial Data Set  
28431754DIA4003**

“A Study on the Effects of Canagliflozin (JNJ-28431754) on Renal Endpoints in Adult  
Participants With Type 2 Diabetes Mellitus (CANVAS-R)”

<b>Product Name</b>	INVOKANA
<b>Active Substance</b>	Canagliflozin
<b>Dataset Type</b>	SDTM
<b>Other Study Identifier</b>	CANVAS-R
<b>Study Code</b>	28431754DIA4003
<b>NCT Number</b>	NCT01989754
<b>Reporting Effort</b>	Final
<b>Version</b>	6.0
<b>Date</b>	September 1, 2023

---

# Contents

<b>Contents</b>	<b>2</b>
<b>1 Introduction</b>	<b>3</b>
1.1 Data Set Model . . . . .	3
1.2 Definitions . . . . .	3
<b>2 Anonymization Process</b>	<b>4</b>
2.1 Use of Software . . . . .	4
2.2 Supporting Documentation . . . . .	4
2.3 Output Format of Anonymized Datasets . . . . .	4
2.4 Transformations . . . . .	4
2.5 Implemented Transformation Types . . . . .	5
<b>3 Conclusions</b>	<b>7</b>
<b>References</b>	<b>8</b>
<b>A Definitions</b>	<b>9</b>
A.1 Acronyms . . . . .	9
A.2 Identifiers . . . . .	9
A.3 Glossary . . . . .	9
<b>B Datasets Delivered in 28431754DIA4003</b>	<b>10</b>

---

# 1 Introduction

The purpose of this project was to perform anonymization of the Janssen 28431754DIA4003 clinical trial data set.

The anonymization of this data set was performed to allow the data to be shared with external research teams. Access to clinical trial data provides opportunities to conduct further research that can help advance medical science and improve patient care. This helps ensure the data provided by study participants are used to maximum effect in the creation of knowledge and improving patient care. The data release is subject to certain criteria being met, including a requirement to effectively anonymize the data.

Statistical anonymization was used to preserve the utility required by recipients, while accounting for the context of the data sharing scenario [2]. Unlike a rules-based framework that removes dates (except years) and aggregates all ages over 89 as 90 or older, such as HIPAA Safe Harbor, this approach is adaptive to population distributions, sample size, and the desired utility of the anonymized data.

The data sharing environment and contracts in place with the data recipient are assumed to be at a level which would result in a Privacy and Security Context Assessment score of High and a Recipient Trust Context Assessment score of Medium.

This report describes the anonymization approach used for the study 28431754DIA4003, based on the re-identification risk determination that was performed on the data.

## 1.1 Data Set Model

The data set described in this report for study 28431754DIA4003 was received in the Study Data Tabulation Model (SDTM) standard. For more information on this standard see <https://www.cdisc.org/standards/foundational/sdtm>

## 1.2 Definitions

Definitions of key terms (such as the different types of identifiers) and acronyms are provided in Section A *Definitions*. Additional terms and definitions are provided elsewhere [1].

---

## 2 Anonymization Process

### 2.1 Use of Software

The analysis described in this report was performed using a re-identification risk measurement software application.

### 2.2 Supporting Documentation

The following documents were provided to assist with the analysis:

- 28431754DIA4003 Transformation Summary
- Annotated CRF
- define

### 2.3 Output Format of Anonymized Datasets

All dataset anonymization was performed within the SAS (Statistical Analysis System) native data file format (extension “.sas7bdat”). Datasets received in SAS version 5 (V5) or version 8 (V8) transport file format (extension “.xpt”) must first be converted to .sas7bdat for processing. Following de-identification, all datasets are converted from .sas7bdat to .xpt for delivery. For datasets originally received in .xpt format, this conversion should not pose a problem. However, for datasets received in non-xpt format, inherent limitations in the .xpt format may require modifications.

Based on the definition of the format, conversion of a dataset to XPT transport file format may require modification of the following in the anonymized datasets:

1. Shortening the dataset names,
2. Shortening variable names in the datasets,
3. Shortening dataset or variable labels,
4. Splitting long character values into new variables.

### 2.4 Transformations

In order to bring the risk of re-identification below the determined threshold, some transformations were required on the dataset. The transformations are described based on the indirect identifiers used in the risk measurement. In all cases, modifications to these indirect identifiers are applied to all other linked fields, e.g. where country is suppressed, fields containing brand- or region-specific drug names will also be suppressed as they are linked to geography.

The anonymization strategy required the following modifications to the original datasets:

---

Identifier	Transformation
Subject IDs (USUBJID)	Masked
Site IDs (SITEID)	Suppressed
Patient dates	PHUSE shifted
Free text	Suppressed
Date of birth	Suppressed
Age	Generalized to 4-year intervals

## 2.5 Implemented Transformation Types

The following data transformations have been applied in this dataset:

**Masking** Masking of the unique subject ID was performed using Format-Preserving Encryption (FPE). This type of encryption creates an encrypted value that has the same length as the original ID.

**Generalization** Reduce the precision of a field.

For this specific project, the age of subjects was generalized to 4-year intervals. Table 1 summarizes the mapping of age to generalized age for age greater or equal to 0 years.

Age (Years)	Generalized Age Value (Years) (AGE)
$0 \leq \text{Age} < 4$	0
$4 \leq \text{Age} < 8$	4
$8 \leq \text{Age} < 12$	8
$12 \leq \text{Age} < 16$	12
...	...
$80 \leq \text{Age} < 84$	80
$84 \leq \text{Age} < 88$	84
$88 \leq \text{Age} < 92$	88
$92 \leq \text{Age} < 96$	92

**Table 1:** Age generalization

**PHUSE date shifting** Offset a date value according to the scheme defined in the Pharmaceutical Users Software Exchange (PHUSE) CDISC SDTM anonymization standard [3]. This scheme determines a delta

---

for each patient based on a difference between a date in the trial available for all patients (in this case the first visit date) and an anchor date (in this case, 17 January 2014).

**Suppression** The original value is replaced with an empty cell. The following types of suppression were applied for this project:

**global suppression (GS):** Occurs when risk measurement determines that no suitable generalized value can be retained and all values in the column are therefore suppressed.

**parameter-value suppression (PV):** Occurs when values in a column are suppressed based on the values of a parameter-column in the same dataset. For example, a vital sign dataset may include a parameter-column specifying the type of measurement such as “systolic blood pressure”, “height”, “weight” and “temperature”, and one or more value-columns containing the values of the measurements (for example, height measured in centimeters when the parameter is “height”). Parameter-value suppression occurs when all values in the value-column associated with one or more identifiers in the parameter-column are suppressed as part of the anonymization strategy.

**targeted suppression (TS):** Occurs when non-standardized values or identifying free-text are suppressed in a column with high data utility, retaining only coded and/or other non-identifying values. Targeted suppression may be used when no other columns in the data set contain the same information as the transformed column, and the clinical trial data set would lose significant utility if the column was suppressed in its entirety.

Please see the file “28431754DIA4003 Transformation Summary.csv” for a catalog of all transformations applied to the dataset.

---

### **3 Conclusions**

The re-identification risk of the Janssen 28431754DIA4003 clinical trial database, after the anonymization as described in this report, is below the data risk threshold given the assumed level of mitigating controls and motives and capacity in the context of the data sharing environment.

---

## References

- [1] Khaled El Emam. *Guide to the De-Identification of Personal Health Information*. CRC Press (Auerbach), 2013.
- [2] International Standards Organization. ISO/IEC 27559:2022: Information security, cybersecurity and privacy protection – Privacy enhancing data de-identification framework. Technical report, ISO, 2022.
- [3] PhUSE De-Identification Working Group. De-Identification Standards for CDISC SDTM 3.2. Technical report, 2015.
- [4] Pierangela Samarati. Protecting Respondents' Identities in Microdata Release. *IEEE Transactions on Knowledge and Data Engineering*, 13(6):1010–1027, 2001.
- [5] L. Sweeney. k-Anonymity: A Model for Protecting Privacy. *International Journal on Uncertainty, Fuzziness and Knowledge-based Systems*, 10(5):557–570, 2002.



---

## A Definitions

### A.1 Acronyms

**FPE** Format-Preserving Encryption

**PHUSE** Pharmaceutical Users Software Exchange

**SDTM** Study Data Tabulation Model

### A.2 Identifiers

It is useful to differentiate among the different types of variables in a disclosed data set or document. The way the variables are handled during the risk measurement and anonymization process will depend on how they are categorized.

A distinction is made among three types of variables [4, 5]:

**Directly identifying variables.** One or more direct identifiers can be used to uniquely identify an individual, either by themselves or in combination with other readily available information. In clinical trial data sets and documents, the only patient direct identifier will likely be the subject ID. There will be direct identifiers pertaining to staff and investigators; however, these are treated differently than patient information.

**Indirectly identifying variables.** The indirect identifiers are attributes that, together with other attributes that can be in the dataset or external to it, enable unique identification of a data subject within a specific operational context.

Examples of indirect identifiers include sex, date of birth or age, locations (such as postal codes, census geography, information about proximity to known or unique landmarks), language spoken at home, ethnic origin, aboriginal identity, total years of schooling, marital status, criminal history, total income, visible minority status, event dates (such as admission, discharge, procedure, death, specimen collection, visit/encounter), codes (such as diagnosis codes, procedure codes, and adverse event codes), country of birth, birth weight, and birth plurality.

**Other variables.** These are the variables that are not really useful for determining an individual's identity. They may be clinically relevant or not.

### A.3 Glossary

**data recipient** The data recipient is the researcher who accesses the anonymized data to perform an analysis.

**Privacy and Security Context Assessment** A questionnaire that evaluates the privacy and security controls in place for a data recipient.

**Recipient Trust Context Assessment** A questionnaire that evaluates the motives, capacity, and contracts in place with regard to data recipient performing a re-identification attack.

---

## B Datasets Delivered in 28431754DIA4003

Dataset	Number of Rows
ADSL	7801
ADTTE	5807
ADTTEAE	100198
ADTTEAEP	92973
ADTTECV	58070
ADTTECVP	75556
ADTTEEF	13618
ADTTEEFP	36541
ADTTEEP	34842
ADTTEEPP	63179
ADTTELIV	22530
AE	4929
CM	367943
CO	100
DA	305169
DM	7801
DS	22298
DV	687
EX	7361
FA	162907
IE	1961
LB	1631722
MH	86360
RELREC	39280
SE	19003
SG	100
SS	1791

---

<b>Dataset</b>	<b>Number of Rows</b>
SU	5843
SUPPAE	19495
SUPPCM	440407
SUPPDA	1220676
SUPPDM	662
SUPPEX	777
SUPPFA	64
SUPPLB	7879354
SUPPSG	65
SUPPSS	550
SUPPSV	6971
SV	77852
TA	6
TE	4
TI	32
TS	73
TV	24
VS	183869
ZR	17439

**Table 2:** List tables considered and the number of rows in each.